

2026 OUTLANDER MAX 6X6 DPS



Granite Grey

ENGINE	850
Type	82 hp / 66 lb-ft, Rotax® 999 cc V-twin, DOHC, liquid-cooled High flow radiator cooling fan of 120W & 500 cm³
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary CVT with work calibration Extra low L / H / N / R / P
Drive Train	Selectable 4WD / 6WD with Visco-Lok QE front differential
Driving Assistance	Work / Standard / Sport modes Intelligent Engine Braking (iEB™) Speed limiter
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm 10 in. (25.2 cm) travel
Front Shocks	Oil shocks (REC calibration)
Rear Suspension	Arched double A-arm with sway bar on middle axle 9.8 in. (24.8 cm) travel
Rear Shocks	Oil shocks (REC calibration)
TIRES & WHEELS	
Front / Rear Tires	XPS Trail King – 28 x 8/10 x 14 in.
Wheels	14 in. aluminum
BRAKES	
Front	OVERSIZED dual 252 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm disc brakes with hydraulic twin-piston calipers

PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS™)
- Selectable 4WD / 6WD with Visco-Lok® QE front differential
- pDrive primary CVT with work calibration and extra low gear
- Engine modes, Intelligent Engine Braking (iEB) technology and speed limiter
- 28 in. XPS Trail King tires with 14 in. aluminum wheels
- Oversized 4-disc braking system
- Full skid plate
- RF Digitally Encoded Security System (D.E.S.S.™)
- 1,000 lb bed capacity
- 1,830 lb towing capacity
- LED headlights and taillights
- Removable passenger seat

DIMENSIONS & CAPACITIES

Estimated Dry Weight*	1,388 lb (631 kg)
L x W x H	123.7 X 48.8 X 55.2 in. (314.3 x 124 x 140.2 cm)
Wheelbase	93.3 in. (237 cm)
Ground Clearance	12.5 in. (31.75 cm)
Seat Height	36.8 in. (93.4 cm)
Rack Capacity	Front: 120 lb (54.4 kg)
Storage Capacity	Front cargo: 8 gal (30 L) Rear cargo: 58 gal (220 L) Rear undercargo: 6.6 gal (25 L) Total: 72.6 gal (275 L)
Towing Capacity	1,830 lb (830 kg)
Bed Capacity	1,000 lb (454 kg)
Fuel Capacity	5.1 gal (19.5 L)

FEATURES

Gauge	7.6 in. wide digital display
Magneto	650 W
Instrumentation	Phone storage
Ignition	RF Digitally Encoded Security System (D.E.S.S.)
Lighting	LED headlights and taillights
Winch	N/A
Seat	Removable passenger seat
Handlebar	Standard
Protection	Full skid plate
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

can-am®

©2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATV Safety Institute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

A BRP BRAND 